



# ALANTRA-P A Versatile Filler-Capper Monoblock

The Alantra P+ is a versatile, accurate and consistent servo piston filler and automatic multi capper for pump caps, trigger caps, screw-on caps and snap-on caps







#### **THROUGHPUT**

· 40-50ppm (different models available)

#### **VERSATILE & ECONOMICAL**

- Height setup changeover via HMI menu
- Toolless format parts, reduced downtime (under 15 minutes toolless changeover)
- Easy access to all machine parts from both sides

## **CAP PROPERTIES**

- Cap types: pump caps, trigger caps, screw-on caps, snap-on caps
- Cap diameter range 20mm to 38mm (can be designed for other diameters)
- Pump tube length range 75mm to
   155mm
- Torque adjustable mechanical torque limiter, individual servo per cap available as an add on option

#### **CONTAINER PROPERTIES**

- Min. height without a cap 80mm (feasibility for smaller sizes subjected to engineering review)
- Max. height without a cap (Screw-On, Snap-On cap) - 220mm (feasibility for larger sizes subjected to engineering review)
- Max. height without a cap (Pump cap) 160mm (feasibility for larger sizes subjected to engineering review)
- Container's diameter range 40mm to 76mm (a feasibility study is required for each specific requirement)

# **FOR MORE DETAILS - CONTACT US:**



sa@shemeshautomation.com



(UK) +44 758 428 1707 (US) +1 920 325 0050 (IL) +972 3 550 9946 (FR) +33 6 1521 0409



www.shemeshautomation.com

#### **FILLING METHODS**

Various filling methods are possible, such as:

- Servo Piston
- Gear pump
- · Other options, please inquire

# **CAPS FEEDER**

- · Integrated cap sorter for screw on
- External feeder for other options

## **MAXIMUM EFFICIENCY**

 No line stoppage in case of cap miss pick by the pick & place system

# QC

 $\cdot\,$  Cap presence and height check QC

# STANDARD SPECIFICATION

- Optional to add-on Industry 4.0 connection
- · Tool free changeovers
- Festo (Germany) pneumatics and Servo systems
- Construction materials: SST304 Structure as a standard (SS316 optional on demand), Anodized AL6061
- SIEMENS HMI & S7-1500 PLC series
   (Allen Bradley optional on demand)
- · BANNER/ SICK/OMRON sensors
- E-stop buttons and safety interlocks wired through CAT IV safety controller
- CE, ANSI, OSHA, NFPA and NEC compliant
- · SEW/Siemens Motors
- · ATEX rating optional on demand

# **INDUSTRIES**

- · Chemicals
- Cosmetics
- Pharmaceuticals
- · Food and Beverage and more

